



BY JOHNSON CONTROLS



Window/Wall Room Air Conditioners

Y9USE07/09-5R-II

YEUSE12-5R-II

YFUSH18/24-5R-II



Window Type R-22

07/09-5R-II & 12-5R-II



Features

- ✓ Cooling & heating
- ✓ Energy optimiser
- ✓ Breeze effect
- ✓ Four way deflection
- ✓ Remote control
- ✓ Timer
- ✓ MEPS Certified
- ✓ 5 Operation modes (Cool/heat/Auto/Dry/Fan)
- ✓ 3 Speed fan control
- ✓ 24 Hour timer

18/24-5R-II



Features

- ✓ Designed for heat pump
- ✓ Powerful cooling & heating
- ✓ Side air-intake, side cooled-air discharge
- ✓ Soft start
- ✓ Washable on-touch filter and easy removal panel
- ✓ Unique quiet design
- ✓ Fresh air switch
- ✓ MEPS Certified
- ✓ Liquid crystal
- ✓ 5 Operation modes (Cool/heat/Auto/Dry/Fan)
- ✓ 3 Speed fan control
- ✓ 24 Hour timer


Technical features

Models	Sizes	Y9USE07-5R-II	Y9USE09-5R-II	YEUSE12-5R-II	YFUSE18-5R-II	YFUSE24-5R-II
Cooling capacity	kW	2.3	2.7	3.8	5.0	5.9
Heating capacity	kW	2.0	2.6	3.5	4.7	5.5
Compressor	Type	Rotary				
Refrigerant		R22				
Power supply	V/Ph/Hz	220-240 / 1 / 50 + E				
Power input (cooling/heating)	kW	0.7 / 0.7	0.9 / 0.8	1.2 / 1.0	1.8 / 1.6	2.1 / 1.9
EER / COP	w/w	3 / 3	3 / 3.2	3.3 / 3.4	2.9 / 3.0	2.9 / 2.9
Energy star rating (cooling/heating)		4 / 3.5	4 / 3.5	5 / 4.5	3.5 / 3.5	4 / 3
Maximum Current	A	4.3	5.4	6.5	10.3	12.7
Indoor airflow (high speed)	m ³ /h	420	500	700	1080	1030
Sound pressure at 1 m (H / M / L)	dB(A)	52 / 49 / 42	54 / 51 / 47	52 / 52 / 49	60 / 57 / 54	61 / 58 / 55
Dimensions	H (mm)	345	380	430	428	428
	W (mm)	450	600	660	660	660
	D (mm)	535	560	637	770	770
Net weight	kg	35	45	56	73	75
Refrigerant charge	g	520	860	1300	1100	1200
Moisture removal	ltr / hour	1.0	1.1	1.3	2.2	2.5
Operating temperature	°C	17 / 30	17 / 30	17 / 30	17 / 30	17 / 30
Ambient temperature	°C	-7 / 45	-7 / 45	-7 / 45	-7 / 43	-7 / 43
Application area	m ²	11-16	14-20	18-26	26-34	29-37

Nominal cooling capacity based on : - Indoor Air Temp. 27°C DB / 19°C WB - Outdoor Air Temp. 35°C DB / 24°C WB

Nominal heating capacity based on : - Indoor Air Temp. 20°C DB / 24°C WB - Outdoor Air Temp. 7°C DB / 6°C WB

Your local distributor/installer:



For installation advise, quotations or more information, contact your friendly qualified York distributor or go to

www.york.com.au